


LETTER

NOTES:

- 1) UL INSULATION SYSTEM E86543-CLASS F 155°C.
- 2) UL RECOGNIZED COMPONENT: FILE # E86403
- 3) ISOLATION TRANSFORMER CONSTRUCTION UL 60601-1 AND CSA C22.2 NO. 601.1-M90: FILE #E178395
- 4) TUV CERTIFIED: EN61558-1 AND EN61558-2-6, "IPOO: FAIL-SAFE SAFETY ISOLATION TRANSFORMER @ "
- 5) CSA CERTIFIED: FILE # LR80864
- 6) 4000 VRMS HIPOT BETWEEN PRIMARY AND (SECONDARY + CORE). 500 VOLTS BETWEEN SECONDARY AND CORE.
- 7) WEIGHT: 1.15 LBS.
- 8) RoHS AND REACH COMPLIANT
- 9) ALL DIMENSIONS ARE IN INCHES.



INDICATE LIKE POLARITY

DWG BY

DATE

8-22-14

1-20-17

NORTH BABYLON N.Y. CUSTOMER MCI TITLE INTERNATIONAL STYLE PC TRANSFORMER DRAWN BY APPRVD BYISCALE DATE DRAWING NUMBER SMS JOW NONE 6-6-12 4-44-7012