



NOTES:

- 1) UL INSULATION SYSTEM E86543-CLASS F 155°C.
- 2) UL RECOGNIZED COMPONENT: FILE # E86403
- 3) ISOLATION TRANSFORMER CONSTRUCTION UL 60601-1 AND CSA C22.2 NO. 601.1-M90: FILE #E178395
- 4) TUV CERTIFIED: EN61558-1 AND EN61558-2-6, "P00: FAIL-SAFE SAFETY ISOLATION TRANSFORMER"
- 5) CSA CERTIFIED: FILE # LR80864
- 6) 4000 VRMS HIPOT BETWEEN PRIMARY AND (SECONDARY + CORE).
- 7) WEIGHT: 7.1 LBS.
- 8) ROHS AND REACH COMPLIANT
- 9) ALL DIMENSIONS ARE IN INCHES.

REVISIONS			DATE
LETTER	DESCRIPTION		
A	CORRECTED MOUNTING DIMENSION & STACK DIMENSION		3-4-19

CUSTOMER	MCI	<i>MCI</i>		BABYLON, NY
TITLE	VDE QUICK CONNECT TRANSFORMER			
DRAWN BY	JDW	APPROVD BY	JDW	SCALE
DATE	2-16-17	DRAWING NUMBER	4-49-0010	