



NOTES:

- 1) UL INSULATION SYSTEM E86543-CLASS F 155°C.
- 2) UL RECOGNIZED COMPONENT: FILE # E86403
- 3) ISOLATION TRANSFORMER CONSTRUCTION UL 60601-1 AND CSA C22.2 NO. 601.1-M90: FILE #E178395
- 4) TUV CERTIFIED: EN61558-1 AND EN61558-2-4, "IPPOO: FAIL-SAFE SAFETY ISOLATION TRANSFORMER"
- 5) CSA CERTIFIED: FILE # LR80864
- 6) 4000 VRMS HIPOT BETWEEN PRIMARY AND (SECONDARY + CORE).
- 7) WEIGHT: 7.1 LBS.
- 8) ROHS AND REACH COMPLIANT
- 9) ALL DIMENSIONS ARE IN INCHES.

REVISIONS		
LETTER	DESCRIPTION	DATE
A	REDRAWN AND UPDATED NOTES	2-16-17
B	CORRECTED MOUNTING DIMENSION & STACK DIMENSION	3-4-19

CUSTOMER	MCI	<i>MCI</i>		BABYLON, NY	
TITLE	VDE QUICK CONNECT TRANSFORMER				
DRAWN BY	APPROVD BY	SCALE	DATE	DRAWING NUMBER	
SMS	JDW	NONE	7-29-15	4-49-0230	